



## DECLARATION OF CONFORMITY

The undersigned, representing the

**STORAENSO TIMBER AB**

and manufacturing plant

**GRUVÖN SAWMILL**

herewith declares that the

**Sawn, planed or profiled panelling and cladding with or without tongue and groove with characteristics and performance declarations as below**

Characteristic	Performance declaration
Intended use	Internal or external panelling/cladding for wall or ceiling
Species/species group	WPPA: spruce ( <i>Picea abies</i> ) and pine ( <i>Pinus sylvestris</i> )
Growth area	NNE Europe (Northern and North Eastern Europe)
Minimum thickness	6 mm
Reaction to fire	D-s2, d2 (CWFT – EN 14915, Table 1; density 390 kg/m <sup>3</sup> ; minimum total thickness 9 mm, minimum thickness 6 mm)
Formaldehyde class	E1
Content of pentachlorophenol	None
Water vapour permeability	60 (see EN 14915, clause 5.4)
Sound absorption coefficient	0,10/0,30 (see EN 14915, clause 5.5)
Thermal conductivity	0,11 (see EN 14915, clause 5.6)
Natural durability class	4 (EN 350-2)

**is in conformity with the provisions of the EC Directive 89/106/CEE (Construction Products Directive - CPD) and that Annex ZA of**

**EN 14915:2006**

**has been applied.**

The CE marking was affixed in 2008.

**STORAENSO TIMBER AB**

**Gruvön Sawmill**

**Timmervägen 1**

**S -664 33 Grums, SWEDEN**

Grums 2008 09 19

Jan-Erik Lindblom

Quality Manager